

EMILUX LIGHTING TECHNOLOGY CO.,LTD

Factory Add:A building,guanhuang road 1#,hengjiaotuo village,gaobu Town,DongGuan City,GuangDong Province,China.523269

[Http://www.emiluxled.com](http://www.emiluxled.com), info@emiluxled.com



LED SPOT LIGHT DATASHEET

EMILUX LIGHTING TECHNOLOGY CO.,LTD

Factory Add:A building,guanhuang road 1#,hengjiaotuo village,gaobu Town,DongGuan City,GuangDong Province,China.523269

[Http://www.emiluxled.com](http://www.emiluxled.com), info@emiluxled.com

Pro Hotel Spot lights



| | |
|-------------------------|-----------------------------------|
| PART NO. | ES4104 |
| DESCRIPTION | Pro hotel Spot lights 10W |
| DATE | 2023.02.06 |
| Dimming optional | triac/0-10v/dali dimming optional |
| Output lumen | 750lm |

EMILUX LIGHTING TECHNOLOGY CO.,LTD

Factory Add:A building,guanhuang road 1#,hengjiaotuo village,gaobu Town,DongGuan City,GuangDong Province,China.523269

[Http://www.emiluxled.com](http://www.emiluxled.com), info@emiluxled.com

● Datasheet:

| | | |
|------------------|--------------------------------|--|
| Type | Product: | Pro hotel Spot light |
| | Model No.: | ES4104 |
| Electronical | Input Voltage: | 220-240V/AC |
| | Frequency: | 50Hz |
| | Power: | 10W |
| | Power Factor: | 0.5 |
| | Total Harmonic Distortion: | < 5% |
| | Certificates: | CE,Rohs,ERP |
| Optical | Cover Material: | PC |
| | Beam Angle: | 15/24/38/60 ° |
| | LED Quantity: | 1pcs |
| | LED Package: | Bridgelux |
| | Luminous Efficiency: | ≥75 |
| | Color Temperature: | 3000K/4000K/5000k |
| | Color Render Index: | 90/95 |
| Lamp Structure | Housing Material: | Aluminium diecasting |
| | Diameter: | Φ 57*85mm |
| | Installation Hole: | Hole Cut 57mm |
| Surface Finished | Finished | powder painting(white color/customized color) |
| Water proof | IP | IP65 |
| Others | Installation Type: | Recessed Type (refer to the Manual) |
| | Application: | Hotels, Supermarkets, Hospital, Aisles, Metro Station, Restaurants, Offices etc. |
| | Ambient Humidity: | ≥80%R.H. |
| | Ambient Temperature: | -10℃ ~ +40℃ |
| | Storage Temperature: | -20℃ ~ 50℃ |
| | Housing Temperature (working): | <70℃ (Ta=25℃) |
| | Lifespan: | 50000H |

EMILUX LIGHTING TECHNOLOGY CO.,LTD

Factory Add:A building,guanhuang road 1#,hengjiaotuo village,gaobu Town,DongGuan City,GuangDong Province,China.523269

[Http://www.emiluxled.com](http://www.emiluxled.com), info@emiluxled.com

Remarks :

1. All pictures&data above are only for your reference, models may slightly differ due to factory operation.
2. According to demand of Energy Star Rules and other Rules, Power Tolerance $\pm 10\%$ and CRI ± 5
- 3.Lumen Output Tolerance 10%
4. Beam Angle Tolerance $\pm 3^\circ$ (angle below 25°) or $\pm 5^\circ$ (angle above 25°)
5. All Data were gained at Ambient Temperature 25°C

- **Dimension:** (unit:mm $\pm 2\text{mm}$, The following picture is a reference picture)

| Model | Diameter ^① (caliber) | Diameter ^② (Maximum outer diameter) | Height ^③ | Suggested Hole Cut | Net Weight (Kg) | Remark |
|--------|------------------------------------|---|------------------------|-----------------------|----------------------|--------|
| ES4104 | 57 | 57 | 85 | 57 | 0.32 | |

- **Installation: (Notes on installation and wiring)**

Please pay more attention to the below instructions while installation, in order to avoid any possible Fire Hazard, Electric Shock or Personal harm.

EMILUX LIGHTING TECHNOLOGY CO.,LTD

Factory Add:A building,guanhuang road 1#,hengjiaotuo village,gaobu Town,DongGuan City,GuangDong Province,China.523269

[Http://www.emiluxled.com](http://www.emiluxled.com), info@emiluxled.com



Instructions:

1. Cut off Electricity before installation.
2. Please do not block any objects on the lamp (distance scale within 70mm), which will definitely affect heat emission while lamp's working
3. Please double check before getting electricity on if wiring is 100% OK, make sure Voltage for lamp is right and no Short-Circuit.

EMILUX LIGHTING TECHNOLOGY CO.,LTD

Factory Add:A building,guanhuang road 1#,hengjiaotuo village,gaobu Town,DongGuan City,GuangDong Province,China.523269

[Http://www.emiluxled.com](http://www.emiluxled.com), info@emiluxled.com


● Wiring:

The Lamp can be directly connected to City Electric Supply and there'll be detailed User's Manual and Wiring Diagram.

Warning:

1. Please strictly follow the instructions while installation to avoid any Hazard or damages.
2. Any installation, check or maintenance should be done by professional, please do not DIY if without enough related knowledge.
3. For better and long performance, please clean the lamp at least every half year with soft cloth. (Do not use Alcohol or Thinner as cleaner which may damage the lamp surface)
4. Do not expose the lamp under strong sunshine, heat sources or other high-temperature places, and storage boxes cannot be piled up exceeding the requirements.

● Carton Box Dimension:



| Package | Dimension) |
|--------------|-------------------------------|
| | LED Downlight |
| Inner Box | 86*86*50mm |
| Outer Box | 420*420*200mm 30PCS/carton |
| Net Weight | 16kg |
| Gross Weight | 17.8kg |

Remarks :

1. If the loading qty less than 48pcs in a carton, pearl cotton material should be used to fill remaining space.
2. Accepted Loading Level is 6 (refer to the actual shown on carton box)
3. The package can be as per customer's specific demand.
4. All package data are only for reference, it may be differ due to actual packing situation.

EMILUX LIGHTING TECHNOLOGY CO.,LTD

Factory Add:A building,guanhuang road 1#,hengjiaotuo village,gaobu Town,DongGuan City,GuangDong Province,China.523269

[Http://www.emiluxled.com](http://www.emiluxled.com), info@emiluxled.com

Application:

Hotels, Supermarkets, Hospital, Aisles, Metro Station, Restaurants, Offices etc.